



## 25° Optic Lens



### Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

### Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

### Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

### Driver

Constant current output LED driver with high efficiency and Pf≥95.

| Type Code       | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz                | Weight (Kg) | Beam Angle |
|-----------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SUSKS.25W.30.25 | 25        | 3000    | 3950              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |
| SUSKS.25W.40.25 | 25        | 4000    | 4150              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |
| SUSKS.35W.30.25 | 35        | 3000    | 5430              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |
| SUSKS.35W.40.25 | 35        | 4000    | 5700              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |
| SUSKS.58W.30.25 | 58        | 3000    | 8780              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |
| SUSKS.58W.40.25 | 58        | 4000    | 9220              | >80 | 220 - 240 / 50 - 60 | 3,5         | 100°/25°   |

