



130° Opal Diffuser



Housing

Aluminium extrusion profile and stainless steel mounting accessories with plastic end cap.

Optics

Optic lens or opal, white, diffusing polycarbonate lens with lambertian light distribution.

Led

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥50.000 hours of lifetime.

Driver

Constant current output LED driver with high efficiency and Pf≥95.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | Weight (Kg) | Beam Angle |
|----------------------|-----------|---------|-------------------|-----|---------------------|-------------|------------|
| SOSKS.25W. 30.130 | 25 | 3000 | 3050 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |
| SOSKS.25W. 40.130 | 25 | 4000 | 3200 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |
| SOSKS.35W. 30.130 | 35 | 3000 | 4380 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |
| SOSKS.35W. 40.130 | 35 | 4000 | 4660 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |
| SOSKS.51W. 30.130 | 51 | 3000 | 6530 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |
| SOSKS.51W. 40.130 | 51 | 4000 | 6930 | >80 | 220 - 240 / 50 - 60 | 3,2 | 130° |

