



# Stella One / Micro

## Housing

Aluminum extrusion profile and steel mounting accessories

## Diffuser

Opal diffusing polycarbonate lens with lambertian light distribution

## LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

## Driver

Constant current output LED driver with high efficiency and Pf≥0.90

## Operating Temperature Range

0 °C/+35 °C


## Option

Dimming via DALI

**LL** Low Lumen

**HL** High Lumen

\*Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 \*Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SSMD.860.12.40	12	4000	1070	80	220 - 240 / 50 - 60	860	LL
SSMD.860.12.30	12	3000	1000	80	220 - 240 / 50 - 60	860	LL
SSMD.860.23.40	23	4000	2130	80	220 - 240 / 50 - 60	860	ML
SSMD.860.23.30	23	4000	2020	80	220 - 240 / 50 - 60	860	ML
SSMD.860.37.40	37	4000	3810	80	220 - 240 / 50 - 60	860	HL
SSMD.860.37.30	37	3000	3610	80	220 - 240 / 50 - 60	860	HL
SSMD.1140.16.40	16	4000	1320	80	220 - 240 / 50 - 60	1140	LL
SSMD.1140.16.30	16	3000	1240	80	220 - 240 / 50 - 60	1140	LL
SSMD.1140.31.40	31	4000	2810	80	220 - 240 / 50 - 60	1140	ML
SSMD.1140.31.30	31	4000	2670	80	220 - 240 / 50 - 60	1140	ML
SSMD.1140.51.40	51	4000	4620	80	220 - 240 / 50 - 60	1140	HL
SSMD.1140.51.30	51	3000	4390	80	220 - 240 / 50 - 60	1140	HL
SSMD.1420.19.40	19	4000	1730	80	220 - 240 / 50 - 60	1420	LL
SSMD.1420.19.30	19	3000	1630	80	220 - 240 / 50 - 60	1420	LL
SSMD.1420.35.40	35	4000	3750	80	220 - 240 / 50 - 60	1420	ML
SSMD.1420.35.30	35	3000	3360	80	220 - 240 / 50 - 60	1420	ML
SSMD.1420.64.40	64	4000	6320	80	220 - 240 / 50 - 60	1420	HL
SSMD.1420.64.30	64	3000	6000	80	220 - 240 / 50 - 60	1420	HL
SSMD.1700.23.40	23	4000	1990	80	220 - 240 / 50 - 60	1700	LL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SSMD.1700.23.30	23	3000	1870	80	220 - 240 / 50 - 60	1700	LL
SSMD.1700.43.40	43	4000	4210	80	220 - 240 / 50 - 60	1700	ML
SSMD.1700.43.30	43	3000	4000	80	220 - 240 / 50 - 60	1700	ML
SSMD.1700.77.40	77	4000	6930	80	220 - 240 / 50 - 60	1700	HL
SSMD.1700.77.30	77	3000	6590	80	220 - 240 / 50 - 60	1700	HL
SSMD.1980.28.40	28	4000	2390	80	220 - 240 / 50 - 60	1980	LL
SSMD.1980.28.30	28	3000	2250	80	220 - 240 / 50 - 60	1980	LL
SSMD.1980.53.40	53	4000	4940	80	220 - 240 / 50 - 60	1980	ML
SSMD.1980.53.30	53	3000	4690	80	220 - 240 / 50 - 60	1980	ML
SSMD.1980.87.40	87	4000	8630	80	220 - 240 / 50 - 60	1980	HL
SSMD.1980.87.30	87	3000	8200	80	220 - 240 / 50 - 60	1980	HL
SSMD.2260.32.40	32	4000	2650	80	220 - 240 / 50 - 60	2260	LL
SSMD.2260.32.30	32	3000	2650	80	220 - 240 / 50 - 60	2260	LL
SSMD.2260.61.40	61	4000	5620	80	220 - 240 / 50 - 60	2260	ML
SSMD.2260.61.30	61	3000	5340	80	220 - 240 / 50 - 60	2260	ML
SSMD.2260.100.40	100	4000	9200	80	220 - 240 / 50 - 60	2260	HL
SSMD.2260.100.30	100	3000	8740	80	220 - 240 / 50 - 60	2260	HL
SSMD.2540.36.40	36	4000	3050	80	220 - 240 / 50 - 60	2540	LL
SSMD.2540.36.30	36	3000	2870	80	220 - 240 / 50 - 60	2540	LL
SSMD.2540.68.40	68	4000	6340	80	220 - 240 / 50 - 60	2540	ML
SSMD.2540.68.30	68	3000	6030	80	220 - 240 / 50 - 60	2540	ML
SSMD.2540.112.40	112	4000	10450	80	220 - 240 / 50 - 60	2540	HL
SSMD.2540.112.30	112	3000	9920	80	220 - 240 / 50 - 60	2540	HL
SSMD.2820.40.40	40	4000	3310	80	220 - 240 / 50 - 60	2820	LL
SSMD.2820.40.30	40	3000	3110	80	220 - 240 / 50 - 60	2820	LL
SSMD.2820.76.40	76	4000	7030	80	220 - 240 / 50 - 60	2820	ML
SSMD.2820.76.30	76	3000	6670	80	220 - 240 / 50 - 60	2820	ML
SSMD.2820.124.40	124	4000	11180	80	220 - 240 / 50 - 60	2820	HL
SSMD.2820.124.30	124	3000	10620	80	220 - 240 / 50 - 60	2820	HL

