Stella Duo-S / Opal



Housing
Aluminum extrusion profile and steel mounting accessories

Diffuser
Opal diffusing polycarbonate lens with lambertian light distribution

LED
High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver
Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range
0 °C/+35 °C

Option
Dimming via DALI

LL Low Lumen
HL High Lumen

- Start modules cannot be used as single. At least one piece Cont/End module is required.
*Matte natural anodized housing, finising G90 custom color.

Ral 9016 Ral 9005 *Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Direct	Indirect	Lumen Variations
SSSTI.1410.49.40	49	4000	5570	80	220 - 240 / 50 - 60	1410	45%	55%	LL
SSSTI.1410.49.30	49	3000	5290	80	220 - 240 / 50 - 60	1410	45%	55%	LL
SSSTI.1410.65.40	65	4000	7730	80	220 - 240 / 50 - 60	1410	45%	55%	HL
SSSTI.1410.65.30	65	3000	7340	80	220 - 240 / 50 - 60	1410	45%	55%	HL
SSRSTI. 6058.40.40	40	4000	4330	80	220 - 240 / 50 - 60		45%	55%	LL
SSRSTI. 6058.40.30	40	3000	4110	80	220 - 240 / 50 - 60		45%	55%	LL
SSRSTI. 6058.54.40	54	4000	5980	80	220 - 240 / 50 - 60		45%	55%	HL
SSRSTI. 6058.54.30	54	3000	5680	80	220 - 240 / 50 - 60		45%	55%	HL
SSLSTI.6058.40.40	40	4000	4330	80	220 - 240 / 50 - 60		45%	55%	LL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Direct	Indirect	Lumen Variations
SSLSTI.6058.40.30	40	3000	4110	80	220 - 240 / 50 - 60		45%	55%	LL
SSLSTI.6058.54.40	54	4000	5980	80	220 - 240 / 50 - 60		45%	55%	HL
SSLSTI.6058.54.30	54	3000	5680	80	220 - 240 / 50 - 60		45%	55%	HL





