



Stella Duo-S / Micro



Housing

Aluminum extrusion profile and steel mounting accessories

Diffuser

Microprismatic diffuser providing homogeneous light distribution

LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range

0 °C/+35 °C

Option

Dimming via DALI

LL Low Lumen - Low UGR

HL High Lumen - Low UGR

- Start modules cannot be used as single. At least one piece Cont/End module is required.

*Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 *Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Direct	Indirect	Lumen Variations
SSSMI.1410.49.40	49	4000	5250	80	220 - 240 / 50 - 60	1410	45%	55%	LL
SSSMI.1410.49.30	49	3000	4940	80	220 - 240 / 50 - 60	1410	45%	55%	LL
SSSMI.1410.65.40	65	4000	7290	80	220 - 240 / 50 - 60	1410	45%	55%	HL
SSSMI.1410.65.30	65	3000	6890	80	220 - 240 / 50 - 60	1410	45%	55%	HL
SSRSMI.6058.40.40	40	4000	4080	80	220 - 240 / 50 - 60		45%	55%	LL
SSRSMI.6058.40.30	40	3000	3880	80	220 - 240 / 50 - 60		45%	55%	LL
SSRSMI.6058.54.40	54	4000	5640	80	220 - 240 / 50 - 60		45%	55%	HL
SSRSMI.6058.54.30	54	3000	5360	80	220 - 240 / 50 - 60		45%	55%	HL
SLSMI.6058.40.40	40	4000	4080	80	220 - 240 / 50 - 60		45%	55%	LL
SLSMI.6058.40.30	40	3000	3880	80	220 - 240 / 50 - 60		45%	55%	LL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Direct	Indirect	Lumen Variations
SSLSMI. 6058.54.40	54	4000	5640	80	220 - 240 / 50 - 60		45%	55%	HL
SSLSMI. 6058.54.30	54	3000	5360	80	220 - 240 / 50 - 60		45%	55%	HL

