



Stella Duo-S / Micro



Housing

Aluminum extrusion profile and steel mounting accessories

Diffuser

Prism structured opal white diffuser with lambertian light distribution and high transmissivity

LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range

0 °C/+35 °C

Option

Dimming via DALI

LL Low Lumen - Low UGR

HL High Lumen - Low UGR

- Start modules cannot be used as single. At least one piece Cont/End module is required.

*Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 *Andz.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | L (mm) | Direct | Indirect | Lumen Variations |
|-------------------|-----------|---------|-------------------|-----|---------------------|--------|--------|----------|------------------|
| SSSMI.1410.49.40 | 49 | 4000 | 5250 | 80 | 220 - 240 / 50 - 60 | 1410 | 45% | 55% | LL |
| SSSMI.1410.49.30 | 49 | 3000 | 4940 | 80 | 220 - 240 / 50 - 60 | 1410 | 45% | 55% | LL |
| SSSMI.1410.65.40 | 65 | 4000 | 7290 | 80 | 220 - 240 / 50 - 60 | 1410 | 45% | 55% | HL |
| SSSMI.1410.65.30 | 65 | 3000 | 6890 | 80 | 220 - 240 / 50 - 60 | 1410 | 45% | 55% | HL |
| SSRSMI.6058.40.40 | 40 | 4000 | 4080 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | LL |
| SSRSMI.6058.40.30 | 40 | 3000 | 3880 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | LL |
| SSRSMI.6058.54.40 | 54 | 4000 | 5640 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | HL |
| SSRSMI.6058.54.30 | 54 | 3000 | 5360 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | HL |
| SLSMI.6058.40.40 | 40 | 4000 | 4080 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | LL |
| SLSMI.6058.40.30 | 40 | 3000 | 3880 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | LL |

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | L (mm) | Direct | Indirect | Lumen Variations |
|-----------------------|-----------|---------|-------------------|-----|------------------------|--------|--------|----------|------------------|
| SSLSMI. 6058.54.40 | 54 | 4000 | 5640 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | HL |
| SSLSMI. 6058.54.30 | 54 | 3000 | 5360 | 80 | 220 - 240 / 50 - 60 | | 45% | 55% | HL |

