Stella One-S / Opal



Housing
Aluminum extrusion profile and steel mounting accessories

Diffuser
Opal diffusing polycarbonate lens with lambertian light distribution

LED
High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver
Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range
0 °C/+35 °C

Option
Dimming via DALI

LL Low Lumen
ML Mideum Lumen
HL High Lumen

- Start modules cannot be used as single. At least one piece Cont/End module is required.
*Matte natural anodized housing, finising G90 custom color.

Ral 9016 Ral 9005 *Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SSSTD.1130.16.40	16	4000	1490	80	220 - 240 / 50 - 60	1130	LL
SSSTD.1130.16.30	16	3000	1400	80	220 - 240 / 50 - 60	1130	LL
SSSTD.1130.31.40	31	4000	2980	80	220 - 240 / 50 - 60	1130	ML
SSSTD.1130.31.30	31	3000	2830	80	220 - 240 / 50 - 60	1130	ML
SSSTD.1130.51.40	51	4000	4900	80	220 - 240 / 50 - 60	1130	HL
SSSTD.1130.51.30	51	3000	4650	80	220 - 240 / 50 - 60	1130	HL
SSRSTD. 6058.16.40	16	4000	1490	80	220 - 240 / 50 - 60		LL
SSRSTD. 6058.16.30	16	3000	1400	80	220 - 240 / 50 - 60		LL
SSRSTD. 6058.31.40	31	4000	2980	80	220 - 240 / 50 - 60		ML
SSRSTD. 6058.31.30	31	3000	2830	80	220 - 240 / 50 - 60		ML
SSRSTD. 6058.51.40	51	4000	4900	80	220 - 240 / 50 - 60		HL
SSRSTD. 6058.51.30	51	3000	4650	80	220 - 240 / 50 - 60		HL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SSLSTD. 6058.16.40	16	4000	1490	80	220 - 240 / 50 - 60		LL
SSLSTD. 6058.16.30	16	3000	1400	80	220 - 240 / 50 - 60		LL
SSLSTD. 6058.31.40	31	4000	2980	80	220 - 240 / 50 - 60		ML
SSLSTD. 6058.31.30	31	3000	2830	80	220 - 240 / 50 - 60		ML
SSLSTD. 6058.51.40	51	4000	4900	80	220 - 240 / 50 - 60		HL
SSLSTD. 6058.51.30	51	3000	4650	80	220 - 240 / 50 - 60		HL





