



Stella One-S / Micro



Housing

Aluminum extrusion profile and steel mounting accessories

Diffuser

Prism structured opal white diffuser with lambertian light distribution and high transmissivity

LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range

0 °C/+35 °C

Option

Dimming via DALI

LL Low Lumen - Low UGR

ML Medium Lumen

HL High Lumen

- Start modules cannot be used as single. At least one piece Cont/End module is required.

*Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 *Andz.

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | L (mm) | Lumen Variations |
|-----------------------|-----------|---------|-------------------|-----|---------------------|--------|------------------|
| SSSMD.1130.16.40 | 16 | 4000 | 1320 | 80 | 220 - 240 / 50 - 60 | 1130 | LL |
| SSSMD.1130.16.30 | 16 | 3000 | 1240 | 80 | 220 - 240 / 50 - 60 | 1130 | LL |
| SSSMD.1130.31.40 | 31 | 4000 | 2810 | 80 | 220 - 240 / 50 - 60 | 1130 | ML |
| SSSMD.1130.31.30 | 31 | 3000 | 2670 | 80 | 220 - 240 / 50 - 60 | 1130 | ML |
| SSSMD.1130.51.40 | 51 | 4000 | 4620 | 80 | 220 - 240 / 50 - 60 | 1130 | HL |
| SSSMD.1130.51.30 | 51 | 3000 | 4390 | 80 | 220 - 240 / 50 - 60 | 1130 | HL |
| SSRSMD. 6058.16.40 | 16 | 4000 | 1320 | 80 | 220 - 240 / 50 - 60 | | LL |
| SSRSMD. 6058.16.30 | 16 | 3000 | 1240 | 80 | 220 - 240 / 50 - 60 | | LL |
| SSRSMD. 6058.31.40 | 31 | 4000 | 2810 | 80 | 220 - 240 / 50 - 60 | | ML |
| SSRSMD. 6058.31.30 | 31 | 3000 | 2670 | 80 | 220 - 240 / 50 - 60 | | ML |
| SSRSMD. 6058.51.40 | 51 | 4000 | 4620 | 80 | 220 - 240 / 50 - 60 | | HL |
| SSRSMD. 6058.51.30 | 51 | 3000 | 4390 | 80 | 220 - 240 / 50 - 60 | | HL |

| Type Code | Power (w) | CCT (K) | Light Output (lm) | CRI | V/Hz | L (mm) | Lumen Variations |
|-----------------------|-----------|---------|-------------------|-----|---------------------|--------|------------------|
| SSLSMD. 6058.16.40 | 16 | 4000 | 1320 | 80 | 220 - 240 / 50 - 60 | | LL |
| SSLSMD. 6058.16.30 | 16 | 3000 | 1240 | 80 | 220 - 240 / 50 - 60 | | LL |
| SSLSMD. 6058.31.40 | 31 | 4000 | 2810 | 80 | 220 - 240 / 50 - 60 | | ML |
| SSLSMD. 6058.31.30 | 31 | 3000 | 2670 | 80 | 220 - 240 / 50 - 60 | | ML |
| SSLSMD. 6058.51.40 | 51 | 4000 | 4620 | 80 | 220 - 240 / 50 - 60 | | HL |
| SSLSMD. 6058.51.30 | 51 | 3000 | 4390 | 80 | 220 - 240 / 50 - 60 | | HL |

