



# Stella Emboss-S / Micro



## Housing

Aluminum extrusion profile and steel mounting accessories

## Diffuser

Prism structured opal white diffuser with lambertian light distribution and high transmissivity

## LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

## Driver

Constant current output LED driver with high efficiency and Pf≥0.90

## Operating Temperature Range

0 °C/+35 °C

## Option

Dimming via DALI

**LL** Low Lumen - Low UGR

**ML** Medium Lumen

**HL** High Lumen

- Start modules cannot be used as single. At least one piece Cont/End module is required.

\*Matte natural anodized housing, finishing G90 custom color.



Ral 9016 Ral 9005 \*Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SDSSMD. 1130.16.40	16	4000	1320	80	220 - 240 / 50 - 60	1130	LL
SDSSMD. 1130.16.30	16	3000	1240	80	220 - 240 / 50 - 60	1130	LL
SDSSMD. 1130.31.40	31	4000	2810	80	220 - 240 / 50 - 60	1130	ML
SDSSMD. 1130.31.30	31	3000	2670	80	220 - 240 / 50 - 60	1130	ML
SDSSMD. 1130.51.40	51	4000	4620	80	220 - 240 / 50 - 60	1130	HL
SDSSMD. 1130.51.30	51	3000	4390	80	220 - 240 / 50 - 60	1130	HL
SDRSMD. 6058.16.40	16	4000	1320	80	220 - 240 / 50 - 60		LL
SDRSMD. 6058.16.30	16	3000	1240	80	220 - 240 / 50 - 60		LL
SDRSMD. 6058.31.40	31	4000	2810	80	220 - 240 / 50 - 60		ML
SDRSMD. 6058.31.30	31	3000	2670	80	220 - 240 / 50 - 60		ML

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SDSRSM. 6058.51.40	51	4000	4620	80	220 - 240 / 50 - 60		HL
SDSRSM. 6058.51.30	51	3000	4390	80	220 - 240 / 50 - 60		HL
SDSLSMD. 6058.16.40	16	4000	1320	80	220 - 240 / 50 - 60		LL
SDSLSMD. 6058.16.30	16	3000	1240	80	220 - 240 / 50 - 60		LL
SDSLSMD. 6058.31.40	31	4000	2810	80	220 - 240 / 50 - 60		ML
SDSLSMD. 6058.31.30	31	3000	2670	80	220 - 240 / 50 - 60		ML
SDSLSMD. 6058.51.40	51	4000	4620	80	220 - 240 / 50 - 60		HL
SDSLSMD. 6058.51.30	51	3000	4390	80	220 - 240 / 50 - 60		HL

