Stella One-C / Micro



Housing
Aluminum extrusion profile and steel mounting accessories

Diffuser
Microprismatic diffuser providing homogeneous light distribution

LED
High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver
Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range
0 °C/+35 °C

Option
Dimming via DALI

LL Low Lumen - Low UGR
ML Medium Lumen - Low UGR
HL High Lumen - Low UGR


- Cont/End modules cannot be used as single. At least one piece Start module is required.
*Matte natural anodized housing.


Ral 9016 Ral 9005 *Andz.


Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SCSMD.1121.16.40	16	4000	1320	80	220 - 240 / 50 - 60	1121	LL
SCSMD.1121.16.30	16	3000	1240	80	220 - 240 / 50 - 60	1121	LL
SCSMD.1121.31.40	31	4000	2810	80	220 - 240 / 50 - 60	1121	ML
SCSMD.1121.31.30	31	3000	2670	80	220 - 240 / 50 - 60	1121	ML
SCSMD.1121.51.40	51	4000	4620	80	220 - 240 / 50 - 60	1121	HL
SCSMD.1121.51.30	51	3000	4390	80	220 - 240 / 50 - 60	1121	HL
SCSMD. 1401.19.40	19	4000	1730	80	220 - 240 / 50 - 60	1401	LL
SCSMD. 1401.19.30	19	3000	1630	80	220 - 240 / 50 - 60	1401	LL
SCSMD. 1401.35.40	35	4000	3530	80	220 - 240 / 50 - 60	1401	ML
SCSMD. 1401.35.30	35	3000	3360	80	220 - 240 / 50 - 60	1401	ML
SCSMD. 1401.64.40	64	4000	5450	80	220 - 240 / 50 - 60	1401	HL
SCSMD. 1401.64.30	64	3000	5170	80	220 - 240 / 50 - 60	1401	HL
SCSMD.	23	4000	1990	80	220 - 240 / 50 - 60	1681	LL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
1681.23.40	23	4000	1990	80	220 - 240 / 50 - 60	1681	LL
SCSMD. 1681.23.30	23	3000	1870	80	220 - 240 / 50 - 60	1681	LL
SCSMD. 1681.42.40	42	4000	4210	80	220 - 240 / 50 - 60	1681	ML
SCSMD. 1681.42.30	42	3000	4000	80	220 - 240 / 50 - 60	1681	ML
SCSMD. 1681.77.40	77	4000	6930	80	220 - 240 / 50 - 60	1681	HL
SCSMD. 1681.77.30	77	3000	6590	80	220 - 240 / 50 - 60	1681	HL
SCSMD. 1961.28.40	28	4000	2390	80	220 - 240 / 50 - 60	1961	LL
SCSMD. 1961.28.30	28	3000	2250	80	220 - 240 / 50 - 60	1961	LL
SCSMD. 1961.53.40	53	4000	4940	80	220 - 240 / 50 - 60	1961	ML
SCSMD. 1961.53.30	53	3000	4690	80	220 - 240 / 50 - 60	1961	ML
SCSMD. 1961.87.40	87	4000	8120	80	220 - 240 / 50 - 60	1961	HL
SCSMD. 1961.87.30	87	3000	7710	80	220 - 240 / 50 - 60	1961	HL
SCSMD. 2241.32.40	32	4000	2650	80	220 - 240 / 50 - 60	2241	LL
SCSMD. 2241.32.30	32	3000	2490	80	220 - 240 / 50 - 60	2241	LL
SCSMD. 2241.61.40	61	4000	5620	80	220 - 240 / 50 - 60	2241	ML
SCSMD. 2241.61.30	61	3000	5340	80	220 - 240 / 50 - 60	2241	ML
SCSMD. 2241.100.40	100	4000	9200	80	220 - 240 / 50 - 60	2241	HL
SCSMD. 2241.100.30	100	3000	8740	80	220 - 240 / 50 - 60	2241	HL
SCSMD. 2521.36.40	36	4000	3050	80	220 - 240 / 50 - 60	2521	LL
SCSMD. 2521.36.30	36	3000	2870	80	220 - 240 / 50 - 60	2521	LL
SCSMD. 2521.68.40	68	4000	6340	80	220 - 240 / 50 - 60	2521	ML
SCSMD. 2521.68.30	68	3000	6030	80	220 - 240 / 50 - 60	2521	ML
SCSMD. 2521.112.40	112	4000	10450	80	220 - 240 / 50 - 60	2521	HL
SCSMD. 2521.112.30	112	3000	9920	80	220 - 240 / 50 - 60	2521	HL

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	L (mm)	Lumen Variations
SCSMD. 2801.40.40	40	4000	3310	80	220 - 240 / 50 - 60	2801	LL
SCSMD. 2801.40.30	40	3000	3110	80	220 - 240 / 50 - 60	2801	LL
SCSMD. 2801.76.40	76	4000	7030	80	220 - 240 / 50 - 60	2801	ML
SCSMD. 2801.76.30	76	3000	5050	80	220 - 240 / 50 - 60	2801	ML
SCSMD. 2801.124.40	124	4000	11180	80	220 - 240 / 50 - 60	2801	HL
SCSMD. 2801.124.30	124	3000	10620	80	220 - 240 / 50 - 60	2801	HL
STRSMD. 6058.16.40	16	4000	1320	80	220 - 240 / 50 - 60		LL
STRSMD. 6058.16.30	16	3000	1240	80	220 - 240 / 50 - 60		LL
STRSMD. 6058.31.40	31	4000	2810	80	220 - 240 / 50 - 60		ML
STRSMD. 6058.31.30	31	3000	2670	80	220 - 240 / 50 - 60		ML
STRSMD. 6058.51.40	51	4000	4620	80	220 - 240 / 50 - 60		HL
STRSMD. 6058.51.30	51	3000	4390	80	220 - 240 / 50 - 60		HL
STLSMD. 6058.16.40	16	4000	1320	80	220 - 240 / 50 - 60		LL
STLSMD. 6058.16.30	16	3000	1230	80	220 - 240 / 50 - 60		LL
STLSMD. 6058.31.40	31	4000	2190	80	220 - 240 / 50 - 60		ML
STLSMD. 6058.31.30	31	3000	2020	80	220 - 240 / 50 - 60		ML
STLSMD. 6058.51.40	51	4000	3640	80	220 - 240 / 50 - 60		HL
STLSMD. 6058.51.30	51	3000	3350	80	220 - 240 / 50 - 60		HL


105°
105°
90°
90°
75°
75°
60°
60°
45°
45°
30°
15°
0°
15°
30°
cd/klm
C0 - C180
C90 - C270


Cont / End
L
Max. 1.5 m
80
55


Cont / End
Right
Cont / End
Left