



Stella Deboss-C / Micro



Housing

Aluminum extrusion profile and steel mounting accessories

Diffuser

Prism structured opal white diffuser with lambertian light distribution and high transmissivity

LED

High-efficacy mid power LED with CRI>80, achieving L90B50 ≥ 50,000 hours of lifetime

Driver

Constant current output LED driver with high efficiency and Pf≥0.90

Operating Temperature Range

0 °C/+35 °C

Option

Dimming via DALI

LL Low Lumen - Low UGR

ML Medium Lumen

HL High Lumen

- Cont/End modules cannot be used as single. At least one piece Start module is required.

*Matte natural anodized housing.



Ral 9016 Ral 9005 *Andz.

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Cut-out Size (mm)	L (mm)	Lumen Variations
GCSMD. 1121.16.40	16	4000	1320	80	220 - 240 / 50 - 60	1121x60	1121	LL
GCSMD. 1121.16.30	16	3000	1240	80	220 - 240 / 50 - 60	1121x60	1121	LL
GCSMD. 1121.31.40	31	4000	2810	80	220 - 240 / 50 - 60	1121x60	1121	ML
GCSMD. 1121.31.30	31	3000	2670	80	220 - 240 / 50 - 60	1121x60	1121	ML
GCSMD. 1121.51.40	51	4000	4620	80	220 - 240 / 50 - 60	1121x60	1121	HL
GCSMD. 1121.51.30	51	3000	4390	80	220 - 240 / 50 - 60	1121x60	1121	HL
GCSMD. 1401.19.40	19	4000	1730	80	220 - 240 / 50 - 60	1401x60	1401	LL
GCSMD. 1401.19.30	19	3000	1630	80	220 - 240 / 50 - 60	1401x60	1401	LL
GCSMD. 1401.35.40	35	4000	3530	80	220 - 240 / 50 - 60	1401x60	1401	ML
GCSMD. 1401.35.30	35	3000	3360	80	220 - 240 / 50 - 60	1401x60	1401	ML

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Cut-out Size (mm)	L (mm)	Lumen Variations
GCSMD. 1401.64.40	64	4000	5450	80	220 - 240 / 50 - 60	1401x60	1401	HL
GCSMD. 1401.64.30	64	3000	5170	80	220 - 240 / 50 - 60	1401x60	1401	HL
GCSMD. 1681.23.40	23	4000	1990	80	220 - 240 / 50 - 60	1681x60	1681	LL
GCSMD. 1681.23.30	23	3000	1870	80	220 - 240 / 50 - 60	1681x60	1681	LL
GCSMD. 1681.43.40	43	4000	4210	80	220 - 240 / 50 - 60	1681x60	1681	ML
GCSMD. 1681.43.30	43	3000	4000	80	220 - 240 / 50 - 60	1681x60	1681	ML
GCSMD. 1681.77.40	77	4000	6930	80	220 - 240 / 50 - 60	1681x60	1681	HL
GCSMD. 1681.77.30	77	3000	6590	80	220 - 240 / 50 - 60	1681x60	1681	HL
GCSMD. 1961.28.40	28	4000	2390	80	220 - 240 / 50 - 60	1961x60	1961	LL
GCSMD. 1961.28.30	28	3000	2250	80	220 - 240 / 50 - 60	1961x60	1961	LL
GCSMD. 1961.53.40	53	4000	4940	80	220 - 240 / 50 - 60	1961x60	1961	ML
GCSMD. 1961.53.30	53	3000	4690	80	220 - 240 / 50 - 60	1961x60	1961	ML
GCSMD. 1961.87.40	87	4000	8120	80	220 - 240 / 50 - 60	1961x60	1961	HL
GCSMD. 1961.87.30	87	3000	7710	80	220 - 240 / 50 - 60	1961x60	1961	HL
GCSMD. 2241.32.40	32	4000	2650	80	220 - 240 / 50 - 60	2241x60	2241	LL
GCSMD. 2241.32.30	32	3000	2490	80	220 - 240 / 50 - 60	2241x60	2241	LL
GCSMD. 2241.61.40	61	4000	5620	80	220 - 240 / 50 - 60	2241x60	2241	ML
GCSMD. 2241.61.30	61	3000	5340	80	220 - 240 / 50 - 60	2241x60	2241	ML
GCSMD. 2241.100.40	100	4000	9200	80	220 - 240 / 50 - 60	2241x60	2241	HL
GCSMD. 2241.100.30	100	3000	8740	80	220 - 240 / 50 - 60	2241x60	2241	HL
GCSMD. 2521.36.40	36	4000	3050	80	220 - 240 / 50 - 60	2521x60	2521	LL
GCSMD. 2521.36.30	36	3000	2870	80	220 - 240 / 50 - 60	2521x60	2521	LL
GCSMD. 2521.68.40	68	4000	6340	80	220 - 240 / 50 - 60	2521x60	2521	ML
GCSMD.	68	3000	6030	80	220 - 240 / 50 - 60	2521x60	2521	ML

Type Code	Power (w)	CCT (K)	Light Output (lm)	CRI	V/Hz	Cut-out Size (mm)	L (mm)	Lumen Variations
2521.68.30	68	3000	6030	80	60	2521x60	2521	ML
GCSMD. 2521.112.40	112	4000	10450	80	220 - 240 / 50 - 60	2521x60	2521	HL
GCSMD. 2521.112.30	112	3000	9920	80	220 - 240 / 50 - 60	2521x60	2521	HL
GCSMD. 2801.40.40	40	4000	3310	80	220 - 240 / 50 - 60	2801x60	2801	LL
GCSMD. 2801.40.30	40	3000	3110	80	220 - 240 / 50 - 60	2801x60	2801	LL
GCSMD. 2801.76.40	76	4000	7030	80	220 - 240 / 50 - 60	2801x60	2801	ML
GCSMD. 2801.76.30	76	3000	6670	80	220 - 240 / 50 - 60	2801x60	2801	ML
GCSMD. 2801.124.40	124	4000	11180	80	220 - 240 / 50 - 60	2801x60	2801	HL
GCSMD. 2801.124.30	124	3000	10620	80	220 - 240 / 50 - 60	2801x60	2801	HL
GTRSMD. 6158.16.40	16	4000	1320	80	220 - 240 / 50 - 60			LL
GTRSMD. 6158.16.30	16	3000	1240	80	220 - 240 / 50 - 60			LL
GTRSMD. 6158.31.40	31	4000	2810	80	220 - 240 / 50 - 60			ML
GTRSMD. 6158.31.30	31	4000	2670	80	220 - 240 / 50 - 60			ML
GTRSMD. 6158.51.40	51	4000	4620	80	220 - 240 / 50 - 60			HL
GTRSMD. 6158.51.30	51	3000	4390	80	220 - 240 / 50 - 60			HL
GTLSMD. 6158.16.40	16	4000	1320	80	220 - 240 / 50 - 60			LL
GTLSMD. 6158.16.30	16	3000	1240	80	220 - 240 / 50 - 60			LL
GTLSMD. 6158.31.40	31	4000	2810	80	220 - 240 / 50 - 60			ML
GTLSMD. 6158.31.30	31	4000	2670	80	220 - 240 / 50 - 60			ML
GTLSMD. 6158.51.40	51	4000	3640	80	220 - 240 / 50 - 60			HL
GTLSMD. 6158.51.30	51	3000	3350	80	220 - 240 / 50 - 60			HL

